



PLT1M-L8-0 Premium Cable Tie

PLT1M-L8-0

Pan-Ty® locking tie, miniature cross section, 4.0" (102mm) length, nylon 6.6, slate/black stripe.

Specifications

Product Type	Premium Cable Tie
Color	Slate/Black
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	4
Overall Length (mm)	102
Body Width (In.)	0.1
Body Width (mm)	2.5
Body Thickness (In.)	0.036
Body Thickness (mm)	0.9
Maximum Bundle Diameter (In.)	0.87
Maximum Bundle Diameter (mm)	22.1
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS
Application	General
Part Features	One-piece, all nylon cable tie accommodate a maximum bundle diameter of 0.82" (21mm).

Packaging Detail

UPC	07498353969
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0043
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.0868