

Specifications



Eaton TLP604TEL

Protect It! 6-Outlet Surge Protector, 4 ft. (1.22 m) Cord, 790 Joules, Tel/Fax/Modem Protection

General specifications

PRODUCT NAME	Eaton Tripp Lite series Protect It surge protector
CATALOG NUMBER	TLP604TEL
UPC	037332095442
PRODUCT LENGTH/DEPTH	1.23 in
PRODUCT HEIGHT	10.8 in
PRODUCT WIDTH	1.85 in
PRODUCT WEIGHT	0.82 lb
COMPLIANCES	RoHS
CERTIFICATIONS	UL 1449 UL 497A CSA Std. C22.2 cUL Listed UL Listed CSA C22.2.
GLOBAL CATALOG	TLP604TEL

Product specifications

STORAGE HUMIDITY RANGE	0% to 90% RH
SURGE STYLE	ST - STRIP
SWITCHES	Combination AC circuit breaker and 2 position red illuminated on/off power switch
TELEPHONE/DSL PROTECTION DETAILS	1 line
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	15
FREQUENCY RATING	50/60 Hz
DIAGNOSTIC LED DETAILS	Built-in LED confirms suppressor "protection present" (green) status
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	GRAY
RECOMMENDED ELECTRICAL SERVICE	120V (110-125V)
SLOT OR HOLE MOUNT MEASUREMENT (CENTER TO CENTER)	Distance between slots = 101 mm; Distance between slot height = 28 mm
STORAGE TEMPERATURE RANGE	5° to 104°F (-15° to 40°C)
TRANSFORMER ACCOMMODATION	Transformer Accommodation
UL1449 LET THROUGH RATING	400V
INPUT CORD DETAILS	SJT
INPUT CORD GAUGE (AWG)	14
POWER CORD COLOR	Light Gray
HOUSING COLOR	Light gray
OUTLET ORIENTATION	Single row
OUTLET SPACING	28.5mm
OUTLETS MEASUREMENT (CENTER TO CENTER)	28.5mm
MATERIAL	Plastic
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R

Resources

BROCHURES

[Surge Protector and Power Strip Specification Brochure \(English\)](#)

[Surge Protectors and Power Strips Brochure](#)

MANUALS AND USER GUIDES

[Owner's Manual for Protect It! ® Surge Protectors \(English\)](#)

[Telecommunications Certification Addendum \(Multi-language\)](#)

[Owner's Manual for Protect It! Surge \(Multi-language\)](#)

PACKAGE CONTENTS	Instruction manual with warranty information TLP604TEL 6-ft. (1.83 m) telephone cord
INPUT NOMINAL VOLTAGE	120 VAC
PRODUCT FEATURES	Automatic Shut-Off Mounting Holes or Slots UL Certified Diagnostic LED(s) Telephone/DSL Protection
PLUG COLOR	White Blue
AC SUPPRESSION JOULE RATING	790
AC SUPPRESSION RESPONSE TIME	< 1 ns
CORD GAUGE TYPE	• 14 gauge • SJT
MAXIMUM SURGE AMPS	35500
OPERATING HUMIDITY RANGE	20% to 85% RH

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

