



Mini-Com® Cat 6 UTP RJ45 Coupler Module, Black

CC688BL

The Mini-Com® Cat 6 UTP RJ45 Coupler Module is designed and 100% factory tested to allow for up to two couplers to be used and meet channel performance requirements. Contacts are plated with 50 microinches of gold for superior performance. The coupler module is compatible with Mini-Com Modular Patch Panels and Faceplates. The coupler is black.

Specifications

Product Type	Jack Module
Performance Level	Category 6
Connector Type	Coupler Module
Termination Style	Coupler
Body Material	Polycarbonate
Contact Material	Plated Phosphor Bronze
Module Type	Mini-Com®
Wiring Scheme	T568A/T568B
Shield Type	Unshielded (UTP)
Sub Brand	Pan-Net®
Maximum Operating Temperature (°C)	75
Maximum Operating Temperature (°F)	167
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	14
Maximum Storage Temperature (°C)	75
Maximum Storage Temperature (°F)	167
Minimum Storage Temperature (°C)	-40
Minimum Storage Temperature (°F)	-40
Resistance Properties	Heat-Resistant
Color	Black
Standards Met	Exceeds Channel Requirements of ANSI/TIA-568.2-D and ISO 11801 Standards for the Respective Category with up to 2 couplers per channel, Meets IEC 60603-7, Supports 2500 Connection Cycles with IEEE 802.3af / 802.3at and 802.3bt Type 3 and Type 4, UL 1863 and UL 2043 and RoHS Compliant.
Overall Depth (In.)	1.09
Overall Depth (mm)	27.7
Overall Height (In.)	0.71

Specifications (continued)

Overall Height (mm)	18
Overall Length (In.)	1.09
Overall Length (mm)	27.7
Overall Width (In.)	0.62
Overall Width (mm)	15.7

Packaging Detail

UPC	07498301781
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0032
Std. Ctn. Qty.	50
Std. Ctn. Volume (cf)	0.1604