



Dome-Top® BC2S-S10-C Locking Clamp Barb Tie, PA6.6, M5, 8.5"L, 50lb, PK100

BC2S-S10-C

The BC2S-S10-C Dome-Top® barb tie clamp tie, features a unique patented design with its round smooth edges. Paired with the stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Standard cross section, 8.5" (216mm) length. Appropriate for Indoor use, made of Nylon 6.6, are natural in color and come in packages of 100.

Specifications

Product Type	Locking Clamp Tie
Sub Brand	Dome-Top®
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	8.5
Overall Length (mm)	216
Body Width (In.)	0.185
Body Width (mm)	4.7
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Screw Size	#10 (M5)
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Mounting Hole Width (In.)	0.4
Mounting Hole Width (mm)	10.2

Specifications (continued)

Mounting Hole Diameter (In.)	0.2
Mounting Hole Diameter (mm)	5.1
Standards Met	UL 62275 Compliant (Type 2, 21), UL Listed (File #E56854)
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E
Application	Used to secure a cable bundle to another surface such a control panel, wall or ceiling.

Packaging Detail

UPC	07498352314
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3207