



Pan-Ty® PLT2M-M30 Cable Tie, Black, High Heat PA6.6, 8"L, 18lb, PK1000

PLT2M-M30

Panduit PLT2M-M30 Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Miniature cross section 8.0" (203mm) length. For Indoor use and high temperature applications, made of heat stabilized Nylon 6.6, are black in color and come in packages of 1000.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor
Material	Nylon 6.6
Material Properties	Heat-Stabilized
Resistance Properties	Heat-Resistant
Overall Length (In.)	8
Overall Length (mm)	203
Body Width (In.)	0.098
Body Width (mm)	2.5
Body Thickness (In.)	0.043
Body Thickness (mm)	1.1
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	115
Maximum Operating Temperature (°F)	239
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498356313
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0866
Std. Ctn. Qty.	25000
Std. Ctn. Volume (cf)	2.1638