



Pan-Plug® Modular Plug, Category 5e, 24-26 AWG, 100 Pack

MP588-C

UTP modular plug, Cat. 5e, 24 AWG, 100 pk.

Specifications

Product Type	Modular Plug
Performance Level	Category 5e
Connector Type	Modular Plug
Body Material	Plastic with Stamped Metal Shield
Contact Material	Gold Plated Phosphor Bronze
Number of Plugs	100
Wiring Scheme	T568A/T568B
Overall Length (In.)	0.88
Overall Length (mm)	22.4
Shield Type	Unshielded (UTP)
Overall Width (In.)	0.46
Overall Width (mm)	11.7
Overall Height (In.)	0.32
Overall Height (mm)	8.1
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	14
Compatible Wire Gauge (AWG)	24-26
Color	Clear
Standards Met	Meet all applicable ANSI/TIA-968-A requirements and exceeds IEC 60603-7 specifications, Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications, RoHS compliant
IP Rating	IP20
Flammability Rating	UL94V-0
Sub Brand	Pan-Plug®

Packaging Detail

UPC	07498374552
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0347
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3474