



Pan-Lug™ LCC10-14BW-L Copper Compression Connectors - Lugs

LCC10-14BW-L

Two-hole, long barrel lug with window, #10 AWG wire, 1/4 stud hole, .75 hole spacing.

Specifications

| | |
|----------------------------------|---|
| Product Type | Compression Lug |
| Lug Type | 2 Stud Hole Lug |
| Base Material | Copper |
| Copper Code Conductor Size (AWG) | 10 |
| Sub Brand | Pan-Lug™ |
| Stud Hole Size (In.) | 1/4 |
| Stud Hole Size (mm) | 6.4 |
| Stud Hole Spacing (In.) | 0.75 |
| Stud Hole Spacing (mm) | 19.1 |
| Barrel Type | Long Barrel Length with Inspection Window |
| Barrel Length (In.) | 0.53 |
| Barrel Length (mm) | 13.5 |
| Tongue Type | Standard |
| Tongue Width (In.) | 0.42 |
| Tongue Width (mm) | 10.7 |
| Tongue Angle | Straight |
| Tongue Thickness (In.) | 0.05 |
| Tongue Thickness (mm) | 1.3 |
| Overall Length (In.) | 2.06 |
| Overall Length (mm) | 52.324 |
| Finish/Coating | Tin-Plated |
| Standards Met | UL listed to 486A-486B File #E52164 and CSA certified C22.2 No. 65-13 |
| UL Temperature Rating (°C) | 90 |
| Maximum Voltage (kV) | 35 |
| Wire Strip Length (In.) | 9/16 |
| Wire Strip Length (mm) | 14.3 |
| Part Features | Tin plated to inhibit corrosion,color coded barrel,inspection window, NEBS level 3. |

Packaging Detail

| | |
|-----------------------|-------------|
| UPC | 07498397386 |
| Std. Pkg. Qty. | 50 |
| Std. Pkg. Volume (cf) | 0.0107 |
| Std. Ctn. Qty. | 0 |
| Std. Ctn. Volume (cf) | 0.0000 |