

Specifications

Eaton PDUH20HVL6

Eaton Tripp Lite series basic PDU, 1PH, 1U, NEMA L6-20P input, 15 ft cord, 3.8kW, 16A, 208/240V, 14 Outlets (12) C13 (2) C19



General specifications

PRODUCT NAME	Eaton Tripp Lite series basic PDU
CATALOG NUMBER	PDUH20HVL6
UPC	037332158970
PRODUCT LENGTH/DEPTH	3.75 in
PRODUCT HEIGHT	1.75 in
PRODUCT WIDTH	17.25 in
PRODUCT WEIGHT	5.28 lb
COMPLIANCES	FCC Class A RoHS
CERTIFICATIONS	NOM UL 62368-1 CSA Std. C22.2

Product specifications

FORM FACTOR	1U
PHASE	Single-phase
AMPERAGE RATING	16A
INPUT CONNECTION	NEMA L6-20P
CORD LENGTH	15 ft
FREQUENCY RATING	50/60 Hz
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)

Resources

BROCHURES

[Rack Models and Specifications Brochure \(Spanish\)](#)

[120V PDU Brochure Specifications \(Spanish\)](#)

[230V Power Distribution Unit \(PDU\) Brochure \(English\)](#)

[120V Power Distribution Unit \(PDU\) Brochure \(English\)](#)

[Integrated Solutions Brochure \(English\)](#)

[120V Power Distribution Unit \(PDU\) Models and Specifications List \(English\)](#)

MANUALS AND USER GUIDES

[Owner's Manual for PDUH20DV and PDUH20HVL6 Rackmount PDU's](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

