



## **IT940-C0 In-Line Cable Tie, Black, UV PA6.6, 6.8"L, 124lb, PK100**

IT940-C0

Panduit In-Line locking ties are easy to use because of their low-profile snag-free heads and a belt-like parallel entry lock. The outside teeth on the tie protect cable jackets and wire insulation. With greater resistance to harsh UV light, these ties can be used in both indoor and outdoor environments. Light-Heavy cross section and 6.8" (173mm) length. Made of Weather Resistant Nylon 6.6, are black in color and come in packages of 100. Install by hand or use Panduit GTH-E tool.

### **Specifications**

Product Type	In-Line Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	6.8
Overall Length (mm)	173
Body Width (In.)	0.35
Body Width (mm)	8.9
Body Thickness (In.)	0.065
Body Thickness (mm)	1.7
Maximum Bundle Diameter (In.)	1.57
Maximum Bundle Diameter (mm)	40
Minimum Bundle Diameter (In.)	0.33
Minimum Bundle Diameter (mm)	8
Minimum Loop Tensile Strength (N)	552
Minimum Loop Tensile Strength (lb)	124
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTH-E

**Specifications (continued)**

Part Features	Parallel-entry tie that threads like a belt (180° entry). 50 pct lower head height than conventional 90° ties. Outside teeth protects cable jacket and wire insulation.
---------------	---

**Packaging Detail**

UPC	07498341493
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0696
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.6962