

Specifications

Eaton PDUMH20

Eaton Tripp Lite series metered outlet PDU, 1PH, 1U, NEMA L5-20/5-20P input, 15 ft cord, 2.4kW, 16A, 120V, 12 Outlets (12) 5-20R



General specifications

PRODUCT NAME	Eaton Tripp Lite series metered outlet PDU
CATALOG NUMBER	PDUMH20
UPC	037332142504
PRODUCT LENGTH/DEPTH	4.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	20 in
PRODUCT WEIGHT	4.6 lb
COMPLIANCES	RoHS TAA Compliant
CERTIFICATIONS	RETIE NOM UL 60950-1

Product specifications

FORM FACTOR	1U
PACKAGE CONTENTS	• PDUMH20 Local Metered rackmount PDU • L5-20R to 5-20P plug adapter • Owner's manual with warranty information
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Horizontal
MATERIAL	Metal
CORD LENGTH	15 ft
AMPERAGE RATING	20A
ELECTRIC CURRENT - MAX	20
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS 5-20R	12
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Digital display reports total PDU output current in amps
OUTPUT RECEPTACLES	5-15/20R
GROUNDING OPTIONS	Back panel grounding lug
MINIMUM REQUIRED RACK DEPTH	9.5 in
OUTLET SPACING	30.20mm
OVERLOAD PROTECTION	20A circuit breaker
RECOMMENDED ELECTRICAL SERVICE	Single-phase 20A 120V service
RECEPTACLES	5-15/20R
INPUT CORD LENGTH	15 ft
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	120V
RELATIVE HUMIDITY	5% to 95% non-condensing
FORM FACTORS SUPPORTED	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation

Resources

	Integrated Solutions Brochure (English) 230V Power Distribution Unit (PDU) Brochure (English) 120V PDU Brochure Specifications (Spanish) 120V Power Distribution Unit (PDU) Models and Specifications List (English) 120V Power Distribution Unit (PDU) Brochure (English)
BROCHURES	
	Power Components for Cisco TelePresence Visio Stencil Single-Phase Power Distribution Units (PDUs) Stencil Preview Single Phase Power Distribution Units (PDUs) Visio Stencil
DRAWINGS	
MANUALS AND USER GUIDES	Owner's Manual for Metered Rack PDU (Multi-language)
PRODUCT PAGE (WEB)	PDUMH20 Tripp Lite Model Page

OUTPUT CAPACITY DETAILS	2.4kW (120V) / 20A total capacity; 16A max per outlet
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PRODUCT HIGHLIGHTS	1U horizontal rackmount; digital current meter NEMA 5-20P / L5-20P input; 15-ft. (4.57 m) line cord 12 NEMA 5-15/20R outlets Local metered single phase 20A 120V PDU Reversible housing; 4.5 in. / 11.4cm depth
PDU PLUG TYPE	NEMA L5-20P NEMA 5-20P 5-20P L5-20P
PDU TYPE	Local metered
PDU INPUT VOLTAGE	120
PDU FORM FACTOR	Horizontal (1U)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

