



Dry-Shrink™ HSTT50-C Heatshrink, Black, PO, 100' L, 0.5" to 0.25" ID, PK1

HSTT50-C

The HSTT50-C Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.50" Diameter x 100' Long (12.7 mm x 30.5 m). Color Black. 1 roll.

Specifications

Product Type	Heat Shrink Tubing
Adhesive Lined	No
Color	Black
Material	Cross-Linked Polyolefin
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.5
Nominal Diameter (mm)	12.7
Nominal Recovered Wall Thickness (In.)	0.025
Nominal Recovered Wall Thickness (mm)	0.6
Sub Brand	Dry-Shrink™
Overall Length (In.)	1200
Overall Length (ft.)	100
Overall Length (m)	30.5
Overall Length (mm)	30500
Resistance Properties	Flame-Retardant
Standards Met	UL: E122770; Mil Spec: AMS-DTL-23053/5 Class 1
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.25
Maximum Recovered Inside Diameter (mm)	6.4
Minimum Expanded Inside Diameter (In.)	0.5
Minimum Expanded Inside Diameter (mm)	12.7

Specifications (continued)

Application	For Dry Locations; Insulating and protecting wires and cables
Part Features	2:1 shrink ratio for dry applications. Provides excellent abrasion protection and color coding. Flexible

Packaging Detail

UPC	07498374705
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.4232
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	4.2315