

BEST SELLER



Cat 6 Punchdown Patch Panel, 48 Ports, 2 RU, Black

DP48688TGY

Cat6 Punchdown Patch Panel, 48 Port, Black.

Specifications

Product Type	Patch Panel Kit
Termination Style	Punchdown
Patch Panel Style	Flat
Performance Level	Category 6
Material	CRS
Wiring Scheme	T568A/T568B
Number of Ports	48
Number of Rack Units	2
Overall Width (In.)	19
Overall Width (mm)	482.6
Overall Depth (In.)	1.17
Overall Depth (mm)	29.7
Overall Height (In.)	3.47
Overall Height (mm)	88.1
Overall Length (In.)	1.17
Overall Length (mm)	29.7
Sub Brand	Pan-Net®
Identification Type	Adhesive Label
Color	Black
Standards Met	Exceeds channel and component requirements of ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E standards at swept frequencies 1 to 250 MHz. Meets all applicable ANSI/TIA-968-A requirements; Meets IEC 60603-7, Supports IEEE 802.3af, 802.3at, and IEEE 802.3bt type 3 and 4 for PoE applications up to 100 W, UL 1863 approved, RoHS Compliant
Maximum Operating Temperature (°C)	65
Maximum Operating Temperature (°F)	149
Minimum Operating Temperature (°C)	-10
Minimum Operating Temperature (°F)	-14

Packaging Detail

UPC	07498303710
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.2332
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	2.3321