



Pan-Punch® Patch Cord

P110PC4IG5MAY

The 110 Patch Cord Assembly, 4 Pair Connector To T568A RJ45 Pan-Plug, 5 Meter is for use with Pan-Punch® 110-style Bases, Connectors and Systems.

Specifications

Application	Used in both voice networks and data local area networks designed for use with unshielded twisted pair copper wire and cable.
Product Type	Patch Cord
Conductor Gauge (AWG)	24
Sub Brand	Pan-Punch®
Performance Level	Category 5e
Conductor Type	Stranded
Cable Construction	U/UTP
Patch Cord Type	Unshielded
Plug Housing Material	Polycarbonate
Connector 1 Type	4-Pair 110 Connector
Connector 2 Type	RJ45 8
Overall Length (m)	5
Wiring Scheme	T568A
Color	International Gray
Standards Met	Exceeds all channel and component requirements of ANSI/TIA-568.2-D Category 5e standard; Meets IEC 60352-4 requirements; IDC connection per TIA-568 requirements; RoHS Compliant
IEC Variant	60352-4
Plug Type	8 Position
RapidID™ Enabled	No
Part Features	Deeper cable channel in the base, Rounded edges on jumper trough, Field terminable patch cord connector, Metal contact retention in connecting block, Legs are molded as part of the base, Base has TIP colors on wire strip and Connecting block has RING colors for wiring identification

Packaging Detail

UPC	07498305752
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0456
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.4563