



Pan-Ty® PLT1.5I-M0 Cable Tie, Black, UV PA6.6, 5.6"L, 40lb, PK1000

PLT1.5I-M0

Panduit PLT1.5I-M0 Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Intermediate cross section, 5.6" (142mm) length. For Indoor/Outdoor use, made of Weather Resistant Nylon 6.6, are black in color and come in packages of 1000.

Specifications

Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	5.6
Overall Length (mm)	142
Body Width (In.)	0.142
Body Width (mm)	3.6
Body Thickness (In.)	0.045
Body Thickness (mm)	1.1
Maximum Bundle Diameter (In.)	1.38
Maximum Bundle Diameter (mm)	35
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	178
Minimum Loop Tensile Strength (lb)	40
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS, PPTS, STS2

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498354145
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.1254
Std. Ctn. Qty.	25000
Std. Ctn. Volume (cf)	3.1343