



FIBERRUNNER® TOP SUPPORT ADJUSTABLE "C", FOR 5/8" THREADED ROD

FR6ACB58

Used to support the 6x4 and 4x4 systems from any new threaded rod extending down directly from the ceiling, grid, or ladder rack system. Two position height adjustments to accommodate system with or without hinged cover. Bracket is secured to threaded rod with two nuts. The pre-assembled slide clamps enable fast assembly to channel. Use 7/16in nut driver on slide clamps, For 5/8in threaded rod.

Specifications

Application	(1) The Fiberrunner 6X4 Routing System is a System of Channel, Fittings and Brackets Designed to Segregate, Route, and Protect Fiber Optic and High PerformanceCopper Cabling. (2) it is Suited for Data Center Applications
Product Type	Top Support Adjustable "C"
Sub Brand	FiberRunner®
Color	Black
For Use With	Fast Assembly to Channel
Includes	(1) Bracket Assembly, (2) 5/8-11 Heavy Hex Nuts, (2) 5/8 Helical Spring LockWashers, (1) 1/4-20 T-Bolt, (1) 1/4 -20 Hex KEPS Lock Nut
Material	Steel
Number of Pieces	7
Overall Height (In.)	8.72
Overall Height (mm)	221.5
Overall Length (In.)	17.74
Overall Length (mm)	450.6
Overall Width (In.)	1.66
Overall Width (mm)	42.2
Standards Met	UL Listed to 2024 Optical Fiber Cable Routing Assemblies, Compliant with the Applicable Tests in Telcordia Gr-63-Core, Network Equipment Building Systems Level 3, LP-CSISPEC-FR
System Dimensions	4x4, 6x4
Angle	90°
Compatible Threaded Rod Size (In.)	0.63
Compatible Threaded Rod Size (mm)	15.9
Series Type	4 x 4 and 6 x 4 FiberRunner Brackets

Packaging Detail

UPC	07498383982
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.3299
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000