

YSE14HHS, Heat Shrink Splice For 16 - 14 AWG

By Burndy
Catalog # [YSE14HHS](#)



Heat Shrink Splice For 16 - 14 AWG.

Features

- Manufactured from tin plated, seamless electrolytic copper tubing with integral barrel for maximum conductivity and tensile strength, plus excellent cable support and strain relief
- Smooth funnel entry provides easy wire insertion
- Transparent heat shrink insulation provides waterproofing and weather resistance

Application

For Splicing Aircraft And Commercial Flexible Cables

General

Catalog Number	YSE14HHS
Connector Type	Seamless Butt Splice
EU RoHS Indicator	Yes
Insulation	Y
Insulation Type	Heat Shrink
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYDENT
Trade Name	HYDENT™
Type	YSE-H, Heat Shrink
UPC	781810525487

Dimensions

Dimension - Inside Diameter inch	0.2 in
Dimension - L Length Overall mm	38 mm
Dimension - Length Overall inch	1.50 in

Dimension - Strip Length inch 11/32 in

Conductor Related

Conductor Range	#14 AWG to #16 AWG
Conductor Size	16 - 14 AWG
Conductor Type	<ul style="list-style-type: none"> • CU C Solid-Size • CU C Str-Size

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	100

Product Assets

- [3D Models - YSE14HHS_MODEL-PDF](#)
- [3D Models - YSE14HHS_MODEL-IGES](#)
- [3D Models - YSE14HHS_MODEL-STEP](#)
- [Catalogs - BURNDY Master Catalog - Section B - Small Compression](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_YSE18HHS_LineArt](#)
- [Sales Drawings - 50094195](#)
- [Specifications - YSE14HHS](#)