

Specifications



Eaton U209-000-R

USB-A to RS232 (DB9) Serial Adapter Cable - (M/M), 5 ft. (1.52 m)

General specifications

PRODUCT NAME	Eaton Tripp Lite series USB adapter
CATALOG NUMBER	U209-000-R
UPC	037332095640
PRODUCT LENGTH/DEPTH	4.7 in
PRODUCT HEIGHT	1 in
PRODUCT WIDTH	4.1 in
PRODUCT WEIGHT	0.001 lb
COMPLIANCES	RoHS CE Marked REACH FCC Compliant
CERTIFICATIONS	EN 55024 EN 55032
GLOBAL CATALOG	U209-000-R

Product specifications

RELATIVE HUMIDITY	0-80% non-condensing
COLOR	Black
CABLE JACKET COLOR	Black
CONNECTOR PLATING	Gold
USB SPECIFICATION	USB 2.0 (up to 480 Mbps)
CABLE JACKET MATERIAL	PVC
SIDEA CONNECTOR1	USB A (MALE)
SIDEB CONNECTOR1	DB9 (MALE)
OPERATING TEMPERATURE	32° to 140°F (0° to 60°C)
OPERATING TEMPERATURE RANGE	32° to 140°F (0° to 60°C)
STORAGE TEMPERATURE RANGE	-4° to 176°F (-20° to 80°C)
SIDEB CONNECTOR3	DB9 (MALE)
HOST CONNECTOR	USB A (MALE)
TECHNOLOGY	Serial USB
NUMBER OF PORTS	1
CABLE OUTER DIAMETER (OD)	5.0 +/- 0.15
MATERIAL	PVC
CABLE LENGTH RANGE	5 – 8ft (1 - 2M)

Resources

BROCHURES	Display Solutions Brochure 230V (English) Global
	U209-000-R Android Host Compatibility List Flyer (English)
	Laptop/Tablet Accessories Brochure (English)
MANUALS AND USER GUIDES	U209-000-R Owner's Manual

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

