



HSEC1.0-X Heat Shrink End Cap

HSEC1.0-X

Heat shrink end cap adhesive lined, 1" (26mm) min. expanded I.D., adhesive lined black cross-linked polyolefin, 10 pc. package quantity.

Specifications

Product Type	Heat Shrink End Cap
Application	Wet Applications. Applications Include Insulating and Protecting Wires and Cables
Color	Black
Material	Cross-Linked Polyolefin
Shrink Ratio	2.5:1
Standards Met	RoHS Compliant
Maximum Operating Temperature (°C)	125
Maximum Operating Temperature (°F)	257
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Maximum Recovered Inside Diameter (In.)	0.45
Maximum Recovered Inside Diameter (mm)	11.4
Minimum Expanded Inside Diameter (In.)	1.15
Minimum Expanded Inside Diameter (mm)	29.2
Nominal Recovered Wall Thickness (In.)	0.11
Nominal Recovered Wall Thickness (mm)	2.8
Overall Length (In.)	2.8
Overall Length (mm)	71.1
Part Features	2.5:1 Shrink ratio, wet applications. Adhesive lined inner wall seals and provides excellent protection against moisture

Packaging Detail

UPC	07498391331
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0705
Std. Ctn. Qty.	100
Std. Ctn. Volume (cf)	0.7051