



## Wet-Shrink™ HSEC0.8-X End Cap, Black, PO, 2.17" L, 0.3" Recovered ID, 0.79" ID

HSEC0.8-X

The HSEC0.8-X Crosslinked Polyolefin Heat Shrink End Cap features an adhesive lined inner wall that seals and provides excellent protection against moisture. Applications include insulating and protecting wires and cables in wet locations. Voltage rating of 600 V. Shrink ratio: 2.5:1 (HSEC). Temperature range: -40°F to 257°F (-40°C to 125°C). Cross-linked Polyolefin. 0.79" (20.1 mm) minimum expanded I.D. Color Black. 10 per package.

### Specifications

Product Type	Heat Shrink End Cap
Application	Wet Applications. Applications Include Insulating and Protecting Wires and Cables
Color	Black
Flammability Rating	None
Material	Cross-Linked Polyolefin
Resistance Properties	Moisture-Resistant
Shrink Ratio	2.5:1
Standards Met	RoHS Compliant
Maximum Operating Temperature (°C)	125
Maximum Operating Temperature (°F)	257
Sub Brand	Wet-Shrink™
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Maximum Recovered Inside Diameter (In.)	0.3
Maximum Recovered Inside Diameter (mm)	7.6
Minimum Expanded Inside Diameter (In.)	0.79
Minimum Expanded Inside Diameter (mm)	20.1
Nominal Recovered Wall Thickness (In.)	0.1
Nominal Recovered Wall Thickness (mm)	2.4
Overall Length (In.)	2.17
Overall Length (mm)	55.1
Part Features	2.5:1 Shrink ratio, wet applications. Adhesive lined inner wall seals and provides excellent protection against moisture

**Packaging Detail**

UPC	07498341572
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0185
Std. Ctn. Qty.	100
Std. Ctn. Volume (cf)	0.1850