



Pan-Wrap™ PW75FR-CY Split Harness Wrap, Natural, FR PE, 0.75" Nom Dia., PK1

PW75FR-CY

The PW75FR-CY Pan-Wrap Split Harness Wrap features a patented slot pattern that provides improved flexibility and abrasion protection in any application. The unique wall design is easy for cable breakouts and reduces the installation time. The large overlap accommodates a wide range of bundle diameters. Temperature range: -4°F – 122°F (-20°C – 50°C). Flame-Retardant Polyethylene. Nominal Diameter: 0.75" (19.1 mm), 100' (30.5 m) long. Color Natural. 1 per package.

Specifications

Application	Abrasion protection solution engineered for flexibility and maximum protection of wires and cables with considerably reduced installation time
Note	Compatible with PWT75 tool.
Product Type	Split Harness Wrap
Sub Brand	Pan-Wrap™
Color	Natural
For Use With	PWT75 Tool
Material	Polyethylene
Maximum Bundle Diameter (In.)	0.81
Minimum Bundle Diameter (In.)	0.55
Maximum Bundle Diameter (mm)	20.6
Minimum Bundle Diameter (mm)	14
Maximum Operating Temperature (°C)	50
Minimum Operating Temperature (°C)	-20
Maximum Operating Temperature (°F)	122
Minimum Operating Temperature (°F)	-4
Nominal Diameter (In.)	0.75
Nominal Diameter (mm)	19.1
Overall Length (ft.)	100
Overall Length (m)	30.5
Resistance Properties	Abrasion-Resistant, Flame-Retardant
Part Features	Patented slot pattern provides improved flexibility and abrasion protection in any application; Unique wall design provides for easy cable breakouts; Reduces installation time; Large overlap accommodates a wide range of bundle diameters

Packaging Detail

UPC	07498310778
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	2.4780
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000