



Basic PDU, 15AMP, 120 VOLT, (12)5-20R, 5-15P

P12B01M

This Panduit™ G5 Basic PDU features (12) 5-20R outlets. It is a 15 amp, 120 V, single phase PDU with a NEMA 5-15P input plug and a 10 foot (3m) power cord. The PDU is black.

Specifications

Note	NA Only
Includes	Mounting Hardware
Product Type	PDU
Mount Orientation	Horizontal
Sub Brand	G5
Rack PDU Type	Basic
Plug Type	NEMA 5-15P
Number of Circuit Breakers	0
Input Voltage (V)	120
Input Amperage (A)	15
Phase	Single Phase
Frequency Compatibility (Hz)	50/60
Input Cord Length (ft.)	3
Input Cord Length (m)	10
Output Receptacles	(12)5-20R
Output Voltage (V)	120
Output Capacity (kW)	1.4
Front Panel Display	No
Network Monitoring Port	No
SNMP Compatibility	No
Network Compatibility	No
Network Card	No
Communications Interface	No
Daisy-Chainable / Cascadable	No
LED Indicators	No
Material	Metal
Finish/Coating	Powder-Coated
Color	Black
Overall Height (In.)	1.7

Specifications (continued)

Overall Height (mm)	44
Overall Width (In.)	17.5
Overall Width (mm)	444
Overall Depth (In.)	2
Overall Depth (mm)	50
Number of Rack Units	1
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	10
Minimum Operating Temperature (°F)	50
Maximum Storage Temperature (°C)	60
Maximum Storage Temperature (°F)	140
Minimum Storage Temperature (°C)	-20
Minimum Storage Temperature (°F)	-4
Compliance Certifications	UL 62368-1, FCC Pat 15 Class A (USA), NOM (Mexico), RETIE (Colombia)
Standards Met	UL Listed File number: E218078
Product Warranty Period (Worldwide)	3 Years

Packaging Detail

UPC	61305626330
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.8158
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000