

SLiC® Fiber Terminal 530 Fiber Terminal, 8 OptiTap adapters, 900um pigtails, 2527 tray (SLFT-530-D-1A-08-EPAA)

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

Part Number:
80611314560

The SLiC® fiber aerial terminal closure is a strand-mount, breathable fiber terminal for fiber-to-the-premises (FTTP) applications. It is designed to be used for in-line, taut-sheath, and butt-splicing configurations. The SLiC 530 terminal closure is composed of two separate chambers: a distribution cable splice chamber and a drop termination chamber. The distribution cable splice chamber houses the fiber splices and stores buffer tube or ribbon fiber slack while the drop termination chamber is used to house all drop terminations. This craft separation feature allows the installer to terminate and maintain the drop without entering the splice chamber. The 530 terminal closure has the capability of handling OptiTap® Adapters, external cable assembly module (ECAM) FD factory-terminated SC APC or SC UPC fiber drops, and direct splicing. The terminal accommodates four, six, eight, or 12 drops.

Features and Benefits

One-piece Construction

Easy installation and allows access to the cable splice without removing the closure or the terminal

Separate splice and drop termination chambers

Allows easy & secure access for service connections and drop maintenance (cleaning & testing) without having to enter the closure splice chamber

Double-walled construction

Durable protection from bending & cracking in the most extreme environments

Quick-release latches

Easy installation and re-entry without the need for special tools

SLiC® Fiber Terminal 530 Fiber Terminal, 8 OptiTap adapters, 900um pigtails, 2527 tray (SLFT-530-D-1A-08-EPAA)

CORNING

Specifications

General Specifications

Application	Carrier Networks, CATV Environments, Customer premises environments
Mounting Type	Aerial Strand Mount
Product Type	FOH Closures

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Design

Capacity (number of splices)	288
Closure Type	Free-Breathing, Butt, In-line
Distribution Port Count	8
Sealing Type	Rubber End Seal

Design - Connector

Connector Type	SC
----------------	----

Dimensions

Height	264.16 mm (10.4 in)
Width	218.44 mm (8.6 in)

Ordering Information

Product Number	80611314560
EAN Code	4059496448540
Units per Delivery	1/1

SLiC® Fiber Terminal 530 Fiber Terminal, 8 OptiTap adapters, 900um pigtails, 2527 tray (SLFT-530-D-1A-08-EPAA)

The Corning logo is a blue square with the word "CORNING" in white, serif, uppercase letters centered within it.

CORNING



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2024 Corning Optical Communications. All rights reserved.