

# Innerduct Couplings



## Innerduct Couplings

### Condu-Grip™ Innerduct Couplings

The one-piece Condu-Grip™ Threaded Coupling is capable of providing an airtight seal up to 150 psi and remains watertight under external pressures up to 50 psi. Field assembly is quick and easy, requiring only basic tools.

Part Number	Nominal Duct Size		Duct Type	Mean Duct O.D.	
	(in)	(mm)		(in)	(mm)
08566520	1.25	32	OD Controlled	1.660	42
08566530	1.50	38	OD Controlled	1.900	48
08566540	2.00	51	OD Controlled	2.375	60





# Innerduct Couplings

CONDEX



## Split Innerduct Couplings

Reusable aluminum coupling for temporarily joining all types of innerduct during the cable blowing process. Other sizes are under development.

Part Number	Nominal Duct Size		Duct Type	Mean Duct O.D.	
	(in)	(mm)		(in)	(mm)
08676712	1.25	32	1¼" SDR 11 & 13.5	1.660	42
08676715	1.50	38	1½" SDR 11 & 13.5	1.900	48

### Replacement Parts

Part Number	Description
08676854	1¼" (32 mm) Seal Kit
08676855	1½" (38 mm) Seal Kit



## Speed Ball Split Coupling

Hinged aluminum split coupling for temporarily joining all types on innerduct during a cable blowing process.

**Note:** Inserts are sold separately.

Part Number	Description
08676844	Hinged Coupling Body

## Insert Specifications

Part Number	Nominal Duct Size		Duct Type	Mean Duct O.D.	
	(in)	(mm)		(in)	(mm)
08676859	1.00	25	1" SDR 11 & 13.5	1.315	33
08676860	1.25	32	1¼" SDR 11 & 13.5	1.660	42
08676861	1.50	38	1½" SDR 11 & 13.5	1.900	48
08676862	2.00	51	2" SDR 11 & 13.5	2.375	60
08676863		40	40 mm	1.575	40
08676864		46	46 mm	1.810	46
08676830	1.50-2.00	38-60	1½" & 2" SDR 11 & 13.5	1.900-2.375	48-60

\*Inserts include rubber seal.

