

Specifications

Eaton PDUMV30



Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, L5-30P input, 10 ft cord, 2.9kW, 24A, 120V, 24 Outlets (24) 5-20R



General specifications

PRODUCT NAME	Eaton Tripp Lite series metered outlet PDU
CATALOG NUMBER	PDUMV30
UPC	037332139337
PRODUCT LENGTH/DEPTH	3.75 in
PRODUCT HEIGHT	63.75 in
PRODUCT WIDTH	2.19 in
PRODUCT WEIGHT	8 lb
COMPLIANCES	FCC Class A RoHS TAA Compliant
CERTIFICATIONS	RETIE UL 62368-1 NOM

Product specifications

FORM FACTOR	0U (Vertical)
PACKAGE CONTENTS	• PDUMV30 63.75 inch basic PDU with owner's manual • Set of 2 bolt-on plug retention brackets and installation hardware • Set of mounting brackets and installation hardware
OPERATING TEMPERATURE	32° to 104°F (0° to 40°C)
MOUNTING DIRECTION	Vertical
MATERIAL	Aluminum
INPUT CONNECTION	NEMA L5-30P
CORD LENGTH	10 ft
AMPERAGE RATING	24A
ELECTRIC CURRENT - MAX	24
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
NUMBER OF OUTPUTS 5-20R	24
FEATURES	Flex Center
FRONT PANEL LCD DISPLAY	Set of 2 digital current meters continuously report PDU output current in amps for Bank 1 (20A max) and Bank 2 (20A max) outlets
OUTPUT RECEPTACLES	5-15/20R
LED INDICATORS	Includes 2 built-in 2-character LED meters to display power consumption of items plugged into each separately breakered 20A loading bank.
OVERLOAD PROTECTION	Two 20A breakers protect 12 outlets each
RECOMMENDED ELECTRICAL SERVICE	Single-phase 30A 120V service
RECEPTACLES	5-15/20R
INPUT CORD LENGTH	10 ft
AMPERAGE RATING	Agency de-rated to 24A

Resources

BROCHURES	120V PDU Brochure Specifications (Spanish)
	120V Power Distribution Unit (PDU) Brochure (English)
	230V Power Distribution Unit (PDU) Brochure (English)
	Integrated Solutions Brochure (English)
DRAWINGS	120V Power Distribution Unit (PDU) Models and Specifications List (English)
	Single Phase Power Distribution Units (PDUs) Visio Stencil
	Single-Phase Power Distribution Units (PDUs) Stencil Preview
	PDUMV30 Submittal Drawing
MANUALS AND USER GUIDES	Owner's Manual for Metered Rack PDU (Multi-language)
PRODUCT PAGE (WEB)	PDUMV30 Tripp Lite Model Page

DETAILS	continuous
OPERATING ELEVATION	0-10000 ft. (0-3000 m)
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
OUTPUT NOMINAL VOLTAGE	120V
RELATIVE HUMIDITY	0-95% non-condensing
FORM FACTORS SUPPORTED	0U vertical installation in equipment racks, plus under-counter and wallmount
OUTPUT CAPACITY DETAILS	2.88kW (120V) / 24A total capacity; 20A max per breakered load bank; 16A max per outlet
OUTPUT CAPACITY (KW)	2.9 kW
STORAGE TEMPERATURE	-22° to 122°F (-30° to 50°C)
PRODUCT HIGHLIGHTS	Local metered single phase 24A 120V, 0U 63.75in / 162cm vertical rackmount PDU Attached 10ft / 3.0m cord with NEMA L5-30P input plug Pair of digital meters report output current in amps for each load bank 24 NEMA 5-15/20R outlets in two separately breakered load banks Toolless button mount and bolt-down bracket installation hardware included
PDU PLUG TYPE	L5-30P
PDU TYPE	Local metered
PDU INPUT VOLTAGE	120
PDU FORM FACTOR	Vertical (0U)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

