

Specifications



Eaton SK3-0

Protect It! 3-Outlet Surge Protector, Direct Plug-In, 660 Joules, 2 Diagnostic LEDs

General specifications

PRODUCT NAME	Eaton Tripp Lite series Protect It surge protector
CATALOG NUMBER	SK3-0
UPC	037332166319
PRODUCT LENGTH/DEPTH	2.1 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	3.8 in
PRODUCT WEIGHT	0.2 lb
COMPLIANCES	RoHS
CERTIFICATIONS	UL 1449
GLOBAL CATALOG	SK3-0

Product specifications

STORAGE HUMIDITY RANGE	0% to 90% RH
SURGE STYLE	DP - DIRECT PLUG-IN
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	15
FREQUENCY RATING	60 Hz
EMI / RFI FILTERING	Yes
IMMUNITY	Conforms to IEE 587/ANSI C62.41
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	GRAY
RECOMMENDED ELECTRICAL SERVICE	120V
STORAGE TEMPERATURE RANGE	5° to 104°F (-15° to 40°C)
TRANSFORMER ACCOMMODATION	Transformer Accommodation
UL1449 LET THROUGH RATING	500, 400, 500
INPUT CORD LENGTH DETAILS	Direct plug-in
MATERIAL	Plastic
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
PACKAGE CONTENTS	SK3-0 surge suppressor
INPUT NOMINAL VOLTAGE	120 VAC
PRODUCT FEATURES	UL Certified Diagnostic LED(s) Automatic Shut-Off
PLUG COLOR	Blue White
AC SUPPRESSION JOULE RATING	660
AC SUPPRESSION RESPONSE TIME	< 1ns
AC SUPPRESSION SURGE CURRENT RATING	27000
MAXIMUM SURGE AMPS	39000
OPERATING HUMIDITY RANGE	20% to 85% RH

Resources

BROCHURES

[Surge Protectors and Power Strips Brochure](#)

[Surge Protector and Power Strip Specification Brochure \(English\)](#)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

