



Pan-Lug™ LCCX6-14B-L Compression Connectors - Lugs

LCCX6-14B-L

Two-hole, flex lug, long barrel, #6 AWG wire, 1/4 stud hole, .75 hole spacing.

Specifications

Product Type	Compression Lug
Base Material	Copper
Class G Copper Flex Conductor Size (AWG)	6
Class H Copper Flex Conductor Size (AWG)	6
Class I Copper Flex Conductor Size (AWG)	6
Class K Copper Flex Conductor Size (AWG)	6
Class M Copper Flex Conductor Size (AWG)	6
Copper Code Conductor Size (AWG)	6
DLO Copper Flex Conductor Size (AWG)	6
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/4
Stud Hole Size (mm)	6.4
Stud Hole Spacing (In.)	0.75
Stud Hole Spacing (mm)	19.1
Barrel Type	Long Barrel Length with Inspection Window
Barrel Length (In.)	1.07
Barrel Length (mm)	27.2
Tongue Type	Standard
Tongue Width (In.)	0.48
Tongue Width (mm)	12.2
Tongue Thickness (In.)	0.08
Tongue Thickness (mm)	2
Overall Length (In.)	2.61
Overall Length (mm)	66.3
Finish/Coating	Tin-Plated
UL Temperature Rating (°C)	90

Specifications (continued)

Maximum Voltage (kV)	35
Color Code	Blue
Panduit Die Index Number	P24
Burndy Die Index Number	7
Wire Strip Length (In.)	1.13
Wire Strip Length (mm)	29
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, beveled wire entry.

Packaging Detail

UPC	07498342538
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0328
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000