



Pan-Lug™ LCCX4-14A-L Comp. Lug, 4, Flex, Tin Plt Copper, Two 1/4" Stud, PK50

LCCX4-14A-L

The LCCX4-14A-L Tin-Plated Copper Compression Lug, two-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified.

Specifications

Inside Diameter (In.)	0.28
Inside Diameter (mm)	7.11
Outer Diameter (In.)	0.38
Outer Diameter (mm)	9.65
Product Type	Compression Lug
Lug Type	2 Stud Hole Lug
Base Material	Copper
Copper Code Conductor Size (AWG)	4
DLO Copper Flex Conductor Size (AWG)	4
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/4
Stud Hole Size (mm)	6.4
Stud Hole Spacing (In.)	0.63
Stud Hole Spacing (mm)	16
Barrel Type	Long Barrel with Inspection Window
Barrel Length (In.)	1.05
Barrel Length (mm)	26.7
Tongue Type	Standard
Tongue Width (In.)	0.55
Tongue Width (mm)	14
Tongue Angle	Straight
Tongue Thickness (In.)	0.09
Tongue Thickness (mm)	2.3
Overall Length (In.)	2.49
Overall Length (mm)	63.246
Finish/Coating	Tin-Plated

Specifications (continued)

Standards Met	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No. 65-13
UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35
Color Code	Gray
Panduit Die Index Number	P29
Burndy Die Index Number	8
T & B Die Index Number	8
Wire Strip Length (In.)	1-1/8
Wire Strip Length (mm)	28.6
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, beveled wire entry.

Packaging Detail

UPC	07498342545
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0314
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000