



## Surface Raceway, T-70 Base, 10 ft, Off-White

T70BIW10

The T-70 raceway base provides solutions for routing low voltage, fiber optic, and/or power cabling along perimeter walls. The T-70 raceway is supplied with pre-punched mounting holes and is tamper resistant. It is 10 ft and Off-White.

### Specifications

Product Type	Surface Raceway Channel
Color	Off White
Fitting Type	Channel
For Use With	T-70 Cover
Raceway Type	Low Voltage
Material	PVC
Mount Method	Screw-On
Overall Height (In.)	1.77
Overall Height (mm)	45
Overall Length (ft.)	10
Overall Length (m)	3
Overall Width (In.)	4.07
Overall Width (mm)	103.4
Internal Area (in <sup>2</sup> )	5.15
Internal Area (mm <sup>2</sup> )	3322.57
Sub Brand	Pan-Way®
Standards Met	CE Compliant, UL5A Listed, UL Listed 95425, UL Listed E116129
Application	Provides Solutions for Routing Low Voltage, Fiber Optic and/or Power Cabling Along Perimeter Walls.T-70 Features the Workstation Outlet Center™ Offset Box, Which Provides an Offset Solution to Maximize Channel Capacity and Outlet Density.
Part Features	T-70 raceway base, 10 ft. length. Overall raceway dimension (T-70 base and cover): 4.07 x 1.77 (103.3mm x 45.0mm) Supplied with pre-punched mounting holes. Compatible with Pan-Way Classic Style snap-on faceplates or NEMA standard 70mm faceplates. Transitions to Panduit T-45 and LD profile raceway.

**Packaging Detail**

UPC	07498370748
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.5566
Std. Ctn. Qty.	60
Std. Ctn. Volume (cf)	3.3394