



## StrongHold™ JP2DW-L20 J-Hook Cable System, .37", Blk, PA 6.6, DropWire, 2", PK50

JP2DW-L20

Panduit JP2DW-L20 J-Hook with Drop Wire and Rod Clip has a patented design, featuring complete horizontal and vertical 1" bend radius control, which prevents pinch points and degradation of cable performance. They are suitable for use in air handling spaces and are UL listed. For use with #12 wire and threaded rod up to 3/8" (9.5mm) in diameter or 1/8" - 1/4" (3.2mm-6.4mm), 2.0" (50.8mm) max. bundle capacity. Made of Nylon 6.6, are black in color, and come in packages of 50.

### Specifications

Application	Route High Performance Communication Cabling in Air Handling Spaces
Product Type	Cable Support
Category 5e Cable Capacity	55
Category 6 Cable Capacity	46
Category 6A Cable Capacity	30
Color	Black
For Use With	#12 Wire and Threaded Rod
Includes	Clip
Material	Nylon 6.6
Maximum Flange Thickness (In.)	0.37
Maximum Flange Thickness (mm)	9.5
Maximum J-Hook Bundle Capacity	50.08
Mount Method	Drop Wire
Overall Height (In.)	6
Overall Height (mm)	152.9
Overall Length (In.)	3.7
Overall Length (mm)	92.9
Overall Width (In.)	3.7
Overall Width (mm)	92.9
Standards Met	UL, cULus Listed, RoHS Compliant
Sub Brand	StrongHold™
Static Load Capacity (kg)	4.5
Static Load Capacity (lb)	10

**Specifications (continued)**

Support Type	J-PRO Pre-Assembled J-Hook System
Part Features	Bend Radius Control, Smooth Pulling Surface

**Packaging Detail**

UPC	07498357115
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	1.2851
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000