

Lightera's Jumper Family for Central Offices, Data Centers, or Other Patching Application

LC, SC, Shuttered SC, SN, MDC, FC, and ST2 Connectors

*** BEAD COMPLIANT
* AVAILABLE**

Features And Benefits


- 100% optically tested in the factory
- Wide variety of connector options and cable options available
- Available in a wide variety of fiber types
- Ultra Polish (UPC) and Angled Polish (APC) available for Single-Mode Connectors
- The LC, SC, ST2 and FC products offer pull proof connections and maintain optical contact under load

Product Description

Patch Cords and Jumpers are used to provide optical connection for fiber optic electronics. The use of the patch cord provides a quick and easy method for routing fiber patches in data centers, head-ends, cellular hubs and central offices. The patch cord can be used in an interconnect or cross-connect path connecting the incoming fibers to the electronic equipment and providing patching within the fiber paths. Patch Cords and Jumpers include simplex, duplex and quadplex (quad) assemblies. Larger fiber counts are available in multifiber type assemblies as connectorized cables and multifiber connector assemblies.

LC Jumper

Lightera offers LC simplex and duplex jumpers, pigtails, and hybrid assemblies. The LC Unibody® Connector used on LC patch cords features a trigger mechanism that allows the connector to be easily engaged and disengaged. The trigger also prevents the plug from snagging when patch cords or jumpers are routed. There are a number of boot options with the LC connector for tight bends and limited mounting space with either a 90 degree clip or short boot and 40 degree boot options. LC patch cords and jumpers are available with 900 μ m tight-buffered optical fiber or 1.6, 2.0, 3.0 and 4.8 mm diameter cordage. The 1.2, 1.6 mm cordage is the smallest in the industry and provides greater jumper density in a fully loaded rack and helps prevent congestion in overhead racks.



SC Jumper

The push-pull mating of the SC connector configuration allows the connector to be easily engaged and disengaged. The connector is easily configured into a duplex connector by the use of the 2A1 clip either from the factory with multimode connections or in the field. The SC connector also offers various boot options including the short boot for use in limited spaces. SC patch cords and jumpers are available with 900 μ m tight-buffered optical fiber or 1.2, 1.6, 2.0, 3.0 and 4.8 mm diameter cordage.



FC Jumper

FC connectors have long been used for specific electronic equipment applications. The connector utilizes a twist on cap that is engaged by the key. The assemblies are available with 900 μ m tight-buffered optical fiber or 1.6, 2.0 and 3.0 mm diameter cordage.



ST Jumper

ST connectors have long been used for data and Department of Transportation (DOT) applications. The connector utilizes a ramped bayonet with a "twist-lock". The assemblies are available with 900 μ m, 1.6 mm, 2.0 mm and 3.0 mm diameter cordage.



Jumper Specifications
Single-Mode

Connector	Insertion Loss Max. Standard Deviation	Return Loss Max.	Temperature Range	Cable Retention
LCU/LCS	0.25/0.05 dB	-55 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
LCA/LAS	0.5/0.05 dB	-65 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
SCU/SCS	0.3/0.05 dB	-55 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
SCA/SAS/SHA	0.5/0.05 dB	-65 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
FCU	0.25/0.05 dB	-55 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
FCA	0.3/0.05 dB	-65 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
ST2	0.5/0.05 dB	-55 dB	-40 to 85	Cordage 20 lb

Multimode

Connector	Insertion Loss Max. Standard Deviation	Return Loss Max.	Temperature Range	Cable Retention
LCU/LCS	0.5/0.05 dB	-20 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
SCU/SCS	0.5/0.05 dB	-20 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
FCU	0.25/0.05 dB	-20 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb
ST2	0.6/0.05 dB	-20 dB	-40 to 85	Cordage 20 lb Pigtails 2 lb

Ordering Information: Jumper Assemblies SMART Coding
Examples

JP3WY001LCULCU003M – Jumper Plenum 3.0 mm AllWave® FLEX Optical Fiber Yellow 1 fiber (Simplex) LCU LCU 3 Meters long
JR2WY002SCSSCA003M – Jumper Riser 2.0 mm AllWave FLEX Optical Fiber Yellow 2 fibers (Zip) SCS SCA 3 Meters long
JV9WY001FCUUNC003M – Jumper Low Smoke PVC 900 µm AllWave FLEX Optical Fiber Yellow 1 fiber FCU UNC (Pigtail) 3 Meters long

Syntax

aaa b c ddd eee fff nnn

aaa = Cable Design	JH1 = LSZH mm JH2 = LSZH 2.0 mm JH3 = LSZH 3.0 mm JH4 = LSZH 4.8 mm (Simplex Only) JH5 = LSZH 4.8 mm I/O (Simplex Only) JHD = LSZH DFX 2.4 mm (Duplex Only) JDN = Dual Rated 3.0 mm I/O (Simplex Only) JD1 = Dual Rated 1.6 mm JD2 = Dual Rated 2.0 mm JD5 = Dual Rated I/O 4.8 mm JP1 = Plenum 1.6 mm JP2 = Plenum 2.0 mm JP3 = Plenum 3.0 mm JP4 = Plenum 4.8 mm (Simplex Only) JPD = Plenum DFX 2.4 mm (Duplex Only) JPO = Plenum Over-Jacket (Duplex Only) JR1 = Riser 1.6 mm JR2 = Riser 2.0 mm JR3 = Riser 3.0 mm JR4 = Riser 4.8 mm (Simplex Only) JR5 = Riser 4.8 mm I/O (Simplex Only) JR8 = Riser 4.8 mm I/O Toneable (Simplex Only) JRA = Riser 1.2 mm JRD = Riser DFX 2.4 mm (Duplex Only) JRV = 3.0 mm Ruggedized I/O (Simplex Only) JU6 = UV Buffer 600 µm (Simplex Only) JU9 = UV Buffer 900 µm (Simplex Only) JV6 = Low Smoke PVC 600 µm (Simplex Only) JV9 = Low Smoke PVC 900 µm (Simplex Only)
b = Fiber Type	B = Blue Tiger (Blue Jacket Only) D = EZ-Bend® (White Jacket Default) K = 50 µm Bend-Insensitive (Orange Jacket Default) L = 62.5 µm Multimode (Orange Jacket Default) W = AllWave FLEX+ (Yellow Jacket Default) 3 = LaserWave 300 Bend-Insensitive 4 = LaserWave FLEX Wideband OM5 (Lime Green Jacket Default) 5 = LaserWave 500 Bend-Insensitive 9 = AllWave FLEX Max (White or Yellow Jacket Default)
c = Jacket Color	B = Blue (Blue Tiger) O = Orange (50 µm & 62.5 µm Multimode) S = Slate (Optional Color 62.5 Multimode) W = White K = Black (Indoor/Outdoor 4.8 mm Cordage) Y = Yellow (AllWave FLEX) A = Aqua (LaserWave 150 G+, 300, 550)
ddd = Fiber Count	001 = Simplex 002 = Duplex Zip 004 = Quad Round Cordage (1.6 mm Sub Units Riser Only)

eeeff = Connector Ends "a" & "b"	LCA = LC Angle Polish (Single-Mode Only) LA4 = LC Angle Polish 40 Degree Boot (Single-Mode Only) LAS = LC Angled Polish Short Boot LC4 = LC Ultra Polish 40 Degree Boot LCU = LC Ultra Polish LCS = LC Ultra Polish Short Boot LCF = LC Ultra Polish Soft Boot (900 µm Only) LCD = LC Ultra Polish Single-Mode Duplex w/ Clip SCA = SC Angle Polish (Single-Mode Only) SAS = SC Angle Polish Short Boot SCU = SC Ultra Polish SCS = SC Ultra Polish Short Boot SHA = Shuttered SC Angle Polish (Single-mode only) ST2 = ST2 Ultra Polish (Use with Plenum Cordage) FCA = FC Angle Polish (Single-Mode Only) FCU = FC Ultra Polish UNC = UNConnectorized (Stub, Pigtail) (End "B" Only)
nnn = Length	001 999
g = Unit of Measure	M = Meters (Minimum: 1 m) C = Centimeters (Minimum: 15 cm Simplex/ 45 cm Duplex) F = Feet (Minimum: 1 ft) I = Inches (Minimum: 6 in. Simplex/ 18 in. Duplex)
Note	Additional colors available upon request. (i.e. V = Violet, G = Green, B = Blue, L = Lime Green)
Contact Information	For additional information please contact your sales representative. You can also visit our website at www.lightera.com or call 1-888-FIBERHELP (1-888-342-3743) USA or 1-770-798-5555 outside the USA. For a full list of our certifications, visit our website.
Trademark Notice and Disclaimer	Lightera reserves the right to make changes to the product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Lightera warranties or specifications relating to any of its products or services.
BEAD Disclaimer	Purchase orders must clearly identify specific products requiring compliance with BABAA for BEAD requirements. BABAA for BEAD compliant products will have unique part numbers to distinguish them from non-compliant versions. For details, refer to the Lightera list of BABAA for BEAD Compliant Products listed at https://www.lightera.com/babaa-for-bead-compliant-products/ Customer is required to comply with all BABAA for BEAD requirements applicable to it. Lightera will, at its sole discretion, fulfill orders requested by Customer and will not be liable for errors in product selection, delivery or warehousing which result in the installation of non-BABAA for BEAD compliant products into BEAD funded infrastructure projects.