



Corr. Loom Tubing Slit, 1.58" (40.0mm) X 10' (3.0m), Black,PK1

CLT150F-X20

The CLT150F-X20 Corrugated Loom Slit Wall Tubing protects cables from impact and abrasion. Features a slit for easy installation onto a bundle of wires or a pre-assembled harness assembly, increasing productivity. Hold in place with cable ties and accessories. Suitable for indoor applications. UL94-HB flammability rating and a maximum temperature rating of 122°F (50°C). Polyethylene. Inside diameter 1.58" (40.0mm). Color Black. 1 per package.

Specifications

Product Type	Corrugated Loom Tubing
Color	Black
Environment	Indoor
Flammability Rating	UL94-HB
Inside Diameter (In.)	1.58
Inside Diameter (mm)	40
Material	Polyethylene
Resistance Properties	Abrasion-Resistant
Maximum Operating Temperature (°C)	50
Minimum Operating Temperature (°C)	-40
Maximum Operating Temperature (°F)	122
Minimum Operating Temperature (°F)	-40
Nominal Diameter (In.)	1.5
Nominal Diameter (mm)	38.1
Outer Diameter (In.)	1.85
Outer Diameter (mm)	47
Overall Length (ft.)	10
Overall Length (m)	3.1
Standards Met	RoHS Compliant
Part Features	Provides protection for cables, crush impact and abrasion resistant

Packaging Detail

UPC	07498382897
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.8359
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000