



T75F-C Spiral Wrap, Natural, PE, 0.625" Min Dia., PK1

T75F-C

The T75F-C Polyethylene Spiral Wrap provides continuous abrasion protection for wires, cables, and tubing. The spiral wrap harnesses multiple cables into a single manageable bundle while allowing for breakouts. Lightweight, flexible, durable protection allows for use with irregular shapes. Rated for use up to 122°F (50°C). 0.75" (19.1 mm) diameter x 100' (30.5 m) long. Bundle Diameter Range 0.625" to 5" (15.9 mm to 127.0 mm). Color Natural.

Specifications

Application	Harness Multiple Cables Into a Single Manageable Bundle; Allows Breakouts of Single/Multiple Cables; Provides Abrasion Protection for Wire, Cables, Hoses, and Tubing
Product Type	Spiral Wrap
Color	Natural
Environment	Indoor
Flammability Rating	UL94-HB
Material	Polyethylene
Resistance Properties	Abrasion-Resistant
Maximum Bundle Diameter (In.)	5
Maximum Bundle Diameter (mm)	127
Maximum Operating Temperature (°C)	50
Maximum Operating Temperature (°F)	122
Minimum Bundle Diameter (In.)	0.625
Minimum Bundle Diameter (mm)	15.9
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Outer Diameter (In.)	0.75
Outer Diameter (mm)	19.1
Overall Length (ft.)	100
Overall Length (m)	30.5
Standards Met	UL Recognized - E141152; UL94HB
Wall Thickness (In.)	0.06
Wall Thickness (mm)	1.65

Specifications (continued)

Part Features	Allows breakouts of single/multiple cables, Provides abrasion protection for wire, cables, hoses and tubing. Multiple colors allow for easy identification of cable bundles. The spiral wrap is reusable.
---------------	---

Packaging Detail

UPC	07498370619
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	2.4780
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000