A LANscape[®] Solutions Product

Applications

- Provides an efficient way to securely mate two connectors
- Utilized for interconnecting or cross-connecting at main cross-connects (MCs), intermediate cross-connects (ICs), telecommunication rooms (TRs) or work areas


Description

Closet Connector Housing Panels are offered in a wide variety of fiber counts for use with the LANscape® Solutions hardware products. The panels are used with factory-installed or field-installable connectors to provide interconnect or cross-connect capability in a housing.

The panels are available with a variety of industry-standard adapter types. All standard LANscape Solutions hardware accepts the Closet Connector Housing Panels (CCH-CP) for a universal, "one-size-fits-all" approach. The closet connector housing panels are designed for applications where specified labeling and connector identification are required. This can be accomplished by the use of colored icons, which come standard on many panels.

Features / Benefits

- Designed to accommodate all industry-standard adapter types
- Universal approach is used; one panel size fits in all standard LANscape Solutions hardware (for example, CCH, PCH, CCS, WCH, ICH, EDC, FZB, SPH, PWH)
- Available in 6-, 8- and 12-fiber count options in most adapter styles; 16- and 24-fiber count options also available in MT-RJ and LC duplex styles; 36-, 72-, 96-, and 144-fiber count options available in MTP® Connector
- Unique color-coded connector labeling system



24-Fiber LC Duplex Connector | Photo LAN661



72-Fiber MTP Connector Panel
| Photo LAN659



12-Fiber ST° Compatible Connector Panel | Photo LAN662



12-Fiber SC Duplex Connector Panel | Photo LAN658



A LANscape[®] Solutions Product

Ordering Information

Select ac	Select adapter/connector code.													
Adapter Code	Fiber Type	Alignment	Housing	UPC/ APC	Fiber/ Adapter	6	Available Fibers/Panel Counts 8 12 16 24 36 72 96 14							
LC Dupl														
A8	62.5 μm Multimode	Ceramic	Composite		2		X	X	X	X				
D3	50 µm Multimode	Ceramic	Composite		2		X	X	X	X				
E4	LOMMF*	Ceramic	Composite		2		X	X	X	X				
A9	Single-mode	Ceramic	Composite	UPC	2		X	X	X	X				
SC Duple			*											
91	62.5 μm Multimode	Metal	Composite		2		X	X						
G7	50 μm Multimode	Ceramic	Composite		2		X	X						
E7	LOMMF	Ceramic	Composite		2		X	X						
59	Single-mode	Ceramic	Composite	UPC	2		X	X						
MT-RJ														
97	62.5 μm Multimode	N/A	Composite		2		X	X	X	X				
G1	50 μm Multimode	N/A	Composite		2		X	X	X	X				
E1	LOMMF	N/A	Composite		2		X	X	X	X				
98	Single-mode	N/A	Composite	UPC	2		X	X	X	X				
SC .														
56	62.5 μm Multimode	Metal	Composite		1	X	X	X						
G6	50 μm Multimode	Ceramic	Composite		1	X	X	X						
E6	LOMMF	Ceramic	Composite		1	X	X	X						
3C	Single-mode	Ceramic	Composite	UPC	1	X	X	X						
6C	Single-mode	Ceramic	Composite	APC	1	X	X	X						
ST® Con	npatible Connector													
25T	62.5 μm Multimode	Metal	Metal		1	X	X	X						
15T	62.5 μm Multimode	Ceramic	Metal		1	X	X	X						
G5	50 MU	Ceramic	Metal		1	X	X	X						
E5	LOMMF	Ceramic	Metal		1	X	X	X						
19T	Single-mode	Ceramic	Metal	UPC	1	X	X	X						
FC														
11	Single-mode	Metal	Metal	UPC	1	X	X	X						
21	Single-mode	Metal	Metal	APC	1	X	X	X						
MTP® C	onnector													
69	62.5 μm Multimode	N/A	Composite		12						X	X	X	X
G3	50 μm Multimode	N/A	Composite		12						X	X	X	X
E3	LOMMF	N/A	Composite		12						X	X	X	X
89	Single-mode	N/A	Composite	UPC	12						X	X	X	X
90	Single-mode	N/A	Composite	APC	12						X	X	X	X
Fiber Type		Housing Co	olor											
62.5 μm Multimode		Beige												
50 μm Multimode		Black												
50 μm LOMMF		Aqua												
Single-mode		Blue												
Single-mode APC		Green												

*LOMMF = Laser-Optimized Multimode Fiber





A LANscape[®] Solutions Product

Ordering Information (continued)

Closet Connector Panels

Use the following options to construct the part number:

1 Select fiber count.

06 = 6 fibers

08 = 8 fibers

12 = 12 fibers

16 = 16 fibers

24 = 24 fibers

36 = 36 fibers

72 = 72 fibers

96 = 96 fibers

E4 = 144 fibers

Confirm fiber count for desired adapter is available in preceding chart.

2 Select adapter code from chart on previous page.

Select adapter code from chart on

previous page.

Pigtailed Closet Connector Panels (pigtail is 3 m long)

Use the following options to construct the part number:

Select fiber count.

06 = 6 fibers

08 = 8 fibers

12 = 12 fibers

16 = 16 fibers

24 = 24 fibers

Confirm fiber count for desired adapter is available in preceeding chart

3 Select fiber type.

MIC° Subunit Cable

(Standard Fiber Cable Option)

KH = Multimode (62.5/125 μm)

CH = Standard 50 µm multimode (50/125 µm)

SH = Laser-optimized multimode (50/125 µm)

RH = Single-mode

Ribbon Fiber

KJ = Multimode (62.5/125 μm)

CJ = Standard 50 μm multimode (50/125 μm)

SJ = Laser-optimized multimode $(50/125 \mu m)$

RJ = Single-mode



A LANscape[®] Solutions Product

Ordering Information (continued)

Colored Icons

Pack of 50 Colored Icons

ICN - _ _ _ _ _

Use the following options to construct the part number:

Select icons.

Blank Icons



YLB = Blank (Yellow)

RDB = Blank (Red)

GRB = Blank (Green)

BLB = Blank (Blue) WTB = Blank (White)

Etched Icons



BLP = Phone (Blue)



RDC = Computer (Red)



GRT = Cable TV (Green)

