FOREIGN VOLTAGE DETECTOR

(FVD)

Features

- Senses voltages without making metallic contact
- Indicates voltage both visually and audibly
- Suppresses 20 Hz ringing and frequencies higher than 200 Hz
- Housed in non-conductive material
- Exceeds dielectric strength test for greater than 20 KV
- UL listed to U.S. and Canadian safety standards
- NEBS compliant for Portable Test and Measurement Equipment
- Made in U.S.A.
- U.S. Patent No. 5,952,820

The Foreign Voltage Detector (FVD) tests for potentially hazardous AC voltage that may be encountered by communications technicians. The FVD warns technicians of hazardous voltage without making metallic contact.

The FVD provides visual indication of the amount of AC being detected on a 10 step bar graph. An audible alarm will sound if the detected AC voltage exceeds 50 volts.

Telco Sales, Inc.[®] 118 Hilltop Business Drive Pelham, AL 35124



There are two models of leather pouches available that can be attached to the technician's tool belt. The Model FVDP is for carrying the FVD, and the Model FVDP3 is for carrying the FVD, scissors and knife.

The FVD replaces the 188A Test Set, but it has many more features. Some of these added features are its light weight, small size, senses voltages without making metallic contact, and suppression of 20 Hz ringing and frequencies higher than 200 Hz.

Telephone: 205-403-0113

Fax: 205-403-0119

E-mail: sales@telco-sales.com

www.telco-sales.com

FVD Specifications

Technical

Range 0 to 200 Vrms

Higher voltages are displayed

as >200 volts

Sensing Type AC only

Frequency 50 to 150 Hz

Display 10 step LED bar graph, Log

response

Audible Warning

Frequency 2800 ± 300 Hz

Level Approximately 75 dba @ 1 foot

Threshold >50 Vrms sensed voltage

Size 1.7" x .9" x 7.8"

Weight 4.8 ounces

Battery

Type One (1) 9 Volt Alkaline

Life > 9 hours continuous when idle

(bar graph LED not activate)

Environmental

Operating -20°C to 50°C at 10% to 95% RH,

non-condensing

Storage -40°C to 85°C at 0 to 100% RH,

non-condensing

Shock &

Vibration TR-EOP-000063 Compliant

Ordering Information

Model FVD/FVDPC Foreign Voltage Detector

with Leather Pouch and

Conductive Cap

Model FVDP Leather Pouch for FVD

Model FVDP3 Multi-Pocket Leather

Pouch for FVD, Scissors

and Knife

Model FVDC Conductive Cap for FVD

Telco Sales, Inc.®

118 Hilltop Business Drive

Pelham, AL 35124

Telephone: 205-403-0113

Fax: 205-403-0119

E-mail: sales@telco-sales.com

www.telco-sales.com



Model FVDP