



Surface Raceway, LD10 Drop Ceiling Fitting, Off-White

DCF10IW-X

The drop ceiling/entrance end fitting allows for running cable directly from the ceiling. It is designed to be used with the LD10 Surface Raceway. . It meets TIA/EIA Standards, is UL Listed and Compliant. It features a snap-on installation, is made of ABS plastic and is Off-White.

Specifications

Product Type	Surface Raceway Fitting
Sub Brand	Pan-Way®
Color	Off White
Fitting Type	Entrance End/Drop Ceiling
For Use With	LD10
Material	ABS
Mount Method	Snap-On
Raceway Type	Low Voltage
Standards Met	UL94V-0, FT4, Meets TIA/EIA Standards, UL Listed / Compliant.
Overall Height (In.)	2.25
Overall Height (mm)	57.2
Overall Length (In.)	2.25
Overall Length (mm)	57.1
Overall Width (In.)	1.6
Overall Width (mm)	40.6
Application	Pan-Way ® LDS Profile Raceway is a Single Channel Non-Hinged Raceway Which Provides Solutions For Routing of Power or Low Voltage Data and Fiber Optic Cabling Along Perimeter Walls. Lds Raceway is the Only Non-Metallic Raceway that is Bendable in Low Volt
Part Features	Drop ceiling/entrance end fitting for low voltage applications only.

Packaging Detail

UPC	07498326247
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.1215
Std. Ctn. Qty.	50
Std. Ctn. Volume (cf)	0.6073