



Dry-Shrink™ HSTT75-48-5C Heat Shrink

HSTT75-48-5C

Thin wall heat shrink, .75" (19.0mm) diameter, clear cross-linked polyolefin, 5 pc. package quantity.

Specifications

Product Type	Heat Shrink Tubing
Adhesive Lined	No
Color	Clear
Material	Cross-Linked Polyolefin
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.75
Nominal Diameter (mm)	19.1
Nominal Recovered Wall Thickness (In.)	0.03
Nominal Recovered Wall Thickness (mm)	0.8
Sub Brand	Dry-Shrink™
Overall Length (In.)	48
Overall Length (ft.)	4
Overall Length (m)	1.2
Overall Length (mm)	1219
Standards Met	UL Recognized, CSA Approved, MIL SPEC
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.375
Maximum Recovered Inside Diameter (mm)	9.5
Minimum Expanded Inside Diameter (In.)	0.75
Minimum Expanded Inside Diameter (mm)	19.1
Application	For Dry Locations

Packaging Detail

UPC	07498390665
Std. Pkg. Qty.	5
Std. Pkg. Volume (cf)	0.1737
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000