



FiberRunner® 1-Port Spillout, Yellow

FR1.5IDELYL

The FiberRunner® 1-Port Spillout is used to route cable into 1.5 inch (38mm) diameter split corrugated tubing directly through a hole cut in the side wall. It is compatible with the 4x4, 6x4, and 12x4 FiberRunner® Channel.

Specifications

Application	Data Centers and Telco Central Offices
Product Type	1-Port Spillout
Sub Brand	FiberRunner®
Bend Radius (In.)	2
Bend Radius (mm)	50.8
For Use With	4x4, 6x4, and 12x4 FiberRunner® Channel
Includes	(1) Spill-Out, (1) Retainer, (1) Drilling Template
Material	Polycarbonate/ABS
Overall Height (In.)	3.12
Overall Height (mm)	79.2
Overall Length (In.)	1.53
Overall Length (mm)	38.9
Overall Width (In.)	5.33
Overall Width (mm)	135.4
Standards Met	RoHS Compliant, UL Listed to 2024 Optical Fiber Cable Routing Assemblies Compliant with the applicable tests in Telcordia GR-63-CORE Network Equipment Building Systems Level 3
System Dimensions	4x4, 6x4, 12x4
Color	Yellow

Packaging Detail

UPC	61305676398
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0489
Std. Ctn. Qty.	5
Std. Ctn. Volume (cf)	0.2446