



## ABMS-A-C Cable Tie Mount, Natural, PA 6.6, Rubber Adh., 1.13x1.13", PK100

ABMS-A-C

Panduit's ABMS-A-C 2-way rubber-based adhesive backed cable tie mounts have been designed for fast installation and long-term performance and reliability. They are made of Nylon 6.6., and can be used with miniature, intermediate, and standard cable ties. Mounts are 1.12" x 1.12" (28.5mm x 28.5mm), white in color and intended for use in indoor environments. They supplied in strips of 2 and come in packages of 500.

## **Specifications**

Application	2 Way Cable Tie Mount, used With Miniature, Intermediate, and Standard Cable Ties
Product Type	Cable Tie Mount
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Maximum Compatible Panel Thickness (In.)	0.04
Maximum Compatible Panel Thickness (mm)	1
Maximum Operating Temperature (°C)	49
Maximum Operating Temperature (°F)	120
Minimum Operating Temperature (°C)	-29
Minimum Operating Temperature (°F)	-20
Mount Method	Adhesive Tape
Mounting Hole Thread Size	#6
Overall Height (In.)	0.17
Overall Height (mm)	4.3
Overall Length (In.)	1.13
Overall Length (mm)	28.7
Overall Width (In.)	1.13
Overall Width (mm)	50.3
Standards Met	CE Compliant, UL Recognized: E136577, RoHS Compliant
Static Load Capacity (kg)	0.272
Static Load Capacity (lb)	0.6
For Use With	Miniature, Intermediate Cross-Section Ties



## **Packaging Detail**

UPC	07498358002
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0539
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.2695