



## Dry-Shrink™ HSTT19-48-Q Heatshrink, Black, PO, 4' L, 0.187" to 0.093" ID, PK25

HSTT19-48-Q

The HSTT19-48-Q Thin Wall Heat Shrink Tubing shrinks around wires, connectors, joints, and terminals when heated to protect against abrasion. Applications include insulating and protecting wires/cables in indoor, dry locations. Shrink ratio: 2:1. Temperature range: -67°F to 275°F (-55°C to 135°C). Flame retardant, cross-linked polyolefin. 0.187" Diameter x 4' Long (4.8 mm x 1.2 m). Color Black. 25 per package.

### Specifications

Product Type	Heat Shrink Tubing
Adhesive Lined	No
Color	Black
Material	Cross-Linked Polyolefin
Maximum Operating Temperature (°C)	135
Maximum Operating Temperature (°F)	275
Minimum Operating Temperature (°C)	-55
Minimum Operating Temperature (°F)	-67
Nominal Diameter (In.)	0.187
Nominal Diameter (mm)	4.8
Nominal Recovered Wall Thickness (In.)	0.02
Nominal Recovered Wall Thickness (mm)	0.5
Sub Brand	Dry-Shrink™
Overall Length (In.)	48
Overall Length (ft.)	4
Overall Length (m)	1.2
Overall Length (mm)	1219.2
Resistance Properties	Flame-Retardant
Standards Met	UL: E122770; Mil Spec: AMS-DTL-23053/5 Class 1
Shrink Ratio	2:1
Shrink Temperature (°C)	90
Shrink Temperature (°F)	194
Maximum Recovered Inside Diameter (In.)	0.093
Maximum Recovered Inside Diameter (mm)	2.4
Minimum Expanded Inside Diameter (In.)	0.187
Minimum Expanded Inside Diameter (mm)	4.8

**Specifications (continued)**

Application	For Dry Locations; Insulating and protecting wires and cables
Part Features	2:1 shrink ratio for dry applications. Provides excellent abrasion protection and color coding. Flexible

**Packaging Detail**

UPC	07498390590
Std. Pkg. Qty.	25
Std. Pkg. Volume (cf)	0.1733
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000