



Weatherproofing Kit for Connectors and Splices, includes butyl rubber and PVC tape

## Product Classification

**Product Type** Weatherproofing tape  
**Ordering Note** CommScope® standard product (Global)

## General Specifications

**Application** Provides additional moisture seal for cable connections  
**Applications per Kit** Four 1/2 in–7/8 in | Twelve 1/2 in–1/2 in | Twelve 1/2 in–7/8 in to device | Two 1/2 in–2-1/4 in  
**Harmonized System (HS) Code** 4005.91.0000 (Compounded Rubber, Unvulcanized in Plates, Sheets and Strip)

## Dimensions

**Nominal Size** 1-1/4 in | 1-5/8 in | 1/2 in | 1/4 in | 2-1/4 in | 3/8 in | 5/8 in | 7/8 in

## Material Specifications

**Material Type** Butyl rubber tape | PVC tape

## Environmental Specifications

**UV Resistance Test Method** Butyl test method in QUV weatherometer cycle of 8 hours UV at 150 °F then 4 hours of condensation at 104 °F | PVC tape test method UL 510, ASTM D1000  
**UV Resistance, minimum with no degradation** ≥1000 hours  
**Weather Resistance Test Method** 04AS00-03.6.0 | MIL-STD-1344A, Method 1002

## Packaging and Weights

**Height, packed** 195.58 mm | 7.7 in

# 221213

---

<b>Width, packed</b>	175.26 mm   6.9 in
<b>Length, packed</b>	96.52 mm   3.8 in
<b>Included</b>	One roll of 2 in PVC tape   Six rolls of 2-1/2 in butyl rubber tape   Two rolls of 3/4 in PVC tape
<b>Packaging quantity</b>	1
<b>Weight, gross</b>	1.52 kg   3.351 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant



## Included Products

- 42615-10 - Butyl Rubber Tape, 24 in
- 9905-41 - Black 3/4 in PVC Tape, 66 ft
- 9905-71 - Black 2 in PVC Tape, 20 ft