



## Corr. Loom Tubing Slit, .75" (19.05mm) x 100', Orange,PK1

CLT75F-C3

The CLT75F-C3 Corrugated Loom Slit Wall Tubing protects cables from impact and abrasion. Features a slit for easy installation onto a bundle of wires or a pre-assembled harness assembly, increasing productivity. Hold in place with cable ties and accessories. Suitable for indoor applications. UL94-HB flammability rating and a maximum temperature rating of 122°F (50°C). Polyethylene. Inside diameter 0.762" (19.35mm). Color Orange. 1 per package.

### Specifications

Product Type	Corrugated Loom Tubing
Color	Orange
Environment	Indoor
Flammability Rating	UL94-HB
Inside Diameter (In.)	0.762
Inside Diameter (mm)	19.35
Material	Polyethylene
Resistance Properties	Impact-Resistant
Maximum Operating Temperature (°C)	50
Minimum Operating Temperature (°C)	-40
Maximum Operating Temperature (°F)	122
Minimum Operating Temperature (°F)	-40
Nominal Diameter (In.)	0.75
Nominal Diameter (mm)	19.05
Outer Diameter (In.)	0.933
Outer Diameter (mm)	23.7
Overall Length (ft.)	100
Overall Length (m)	30.5
Standards Met	RoHS Compliant
Part Features	Provides protection for cables, crush impact and abrasion resistant

**Packaging Detail**

UPC	07498362754
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	2.4780
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000