



Pan-Lug™ LCD4-14BF-L Copper Compression Connectors - Lugs

LCD4-14BF-L

Two-hole, standard barrel lug with window, #4 — #3 AWG STR, #2 AWG SOL wire, 1/4 stud hole, .75 hole spacing, 90° angle tongue.

Specifications

Product Type	Compression Lug
Base Material	Copper
Copper Code Conductor Size (AWG)	4
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/4
Stud Hole Size (mm)	6.4
Stud Hole Spacing (In.)	0.75
Stud Hole Spacing (mm)	19.1
Barrel Type	Standard Barrel Length with Inspection Window
Barrel Length (In.)	0.81
Barrel Length (mm)	20.6
Tongue Type	Standard
Tongue Width (In.)	0.55
Tongue Width (mm)	14
Tongue Thickness (In.)	0.09
Tongue Thickness (mm)	2.3
Overall Length (In.)	1.87
Overall Length (mm)	47.5
Finish/Coating	Tin-Plated
UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35
Color Code	Gray
Panduit Die Index Number	P29
Burndy Die Index Number	8
Wire Strip Length (mm)	22.2
Part Features	Tin plated to inhibit corrosion,color coded barrel,inspection window, NEBS level 3.

Packaging Detail

UPC	07498356773
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0377
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000