



Pan-Lug™ LCC350-12-X Comp. Lug, 350, Tin Plt Copper, Strt, Two 1/2" Stud, PK10

LCC350-12-X

The LCC350-12-X Tin-Plated Copper Compression Lug, two-hole, long barrel, has color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection. The long barrel maximizes the number of crimps and provides premium wire pull-out strength and performance. The generously beveled wire entry prevents bent back strands when inserting the conductor into the barrel. UL Listed and CSA Certified.

Specifications

Inside Diameter (In.)	0.7
Inside Diameter (mm)	17.78
Outer Diameter (In.)	0.88
Outer Diameter (mm)	22.35
Product Type	Compression Lug
Lug Type	2 Stud Hole Lug
Base Material	Copper
Copper Code Conductor Size (kcmil)	350
Sub Brand	Pan-Lug™
Stud Hole Size (In.)	1/2
Stud Hole Size (mm)	12.7
Stud Hole Spacing (In.)	1.75
Stud Hole Spacing (mm)	44.5
Barrel Type	Long Barrel without Inspection Window
Barrel Length (In.)	2.24
Barrel Length (mm)	56.9
Tongue Type	Standard
Tongue Width (In.)	1.28
Tongue Width (mm)	32.5
Tongue Angle	Straight
Tongue Thickness (In.)	0.17
Tongue Thickness (mm)	4.3
Overall Length (In.)	5.99
Overall Length (mm)	152.146
Finish/Coating	Tin-Plated
Standards Met	UL listed to 486A-486B File #E52164 and CSA certified C22.2 No. 65-13

Specifications (continued)

UL Temperature Rating (°C)	90
Maximum Voltage (kV)	35
Color Code	Red
Panduit Die Index Number	P71
Burndy Die Index Number	18
T & B Die Index Number	71
Wire Strip Length (In.)	2-5/16
Wire Strip Length (mm)	58.7
Part Features	Tin plated to inhibit corrosion,color coded barrel, NEBS level 3.

Packaging Detail

UPC	07498390255
Std. Pkg. Qty.	10
Std. Pkg. Volume (cf)	0.0528
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000