

Specifications



Eaton SPIKECUBE

1-Outlet Personal Surge Protector, Direct Plug-In, 600 Joules, 2 Diagnostic LEDs

General specifications

PRODUCT NAME	Eaton Tripp Lite series Protect It surge protector
CATALOG NUMBER	SPIKECUBE
UPC	037332010643
PRODUCT LENGTH/DEPTH	1.8 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	1.9 in
PRODUCT WEIGHT	0.11 lb
COMPLIANCES	RoHS
CERTIFICATIONS	UL 1449 UL Listed cUL Listed
GLOBAL CATALOG	SPIKECUBE

Product specifications

STORAGE HUMIDITY RANGE	0% to 90% RH
SURGE STYLE	DP - DIRECT PLUG-IN
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	15
FREQUENCY RATING	50/60 Hz
DIAGNOSTIC LED DETAILS	Protected (green) & Grounded (red)
FORM FACTOR	Direct plug in suppressor supports wall-mounting directly into AC receptacle
OPERATING TEMPERATURE RANGE	32° to 104°F (0° to 40°C)
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	GRAY
RECOMMENDED ELECTRICAL SERVICE	120V (110-125V)
STORAGE TEMPERATURE RANGE	5° to 104°F (-15° to 40°C)
TRANSFORMER ACCOMMODATION	Transformer Accommodation
UL1449 LET THROUGH RATING	400, 500, 500
INPUT CORD LENGTH DETAILS	Direct plug-in
HOUSING COLOR	Light gray Gray
MATERIAL	Plastic
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
PACKAGE CONTENTS	Warranty and instruction information SPIKECUBE Surge Suppressor
INPUT NOMINAL VOLTAGE	120 VAC
PRODUCT FEATURES	Diagnostic LED(s) UL Certified
PLUG COLOR	Blue White
AC SUPPRESSION JOULE RATING	600
AC SUPPRESSION RESPONSE TIME	< 1 ns

Resources

BROCHURES

[Surge Protector and Power Strip Specification Brochure \(English\)](#)

[Surge Protectors and Power Strips Brochure](#)

MAXIMUM SURGE AMPS	36000
OPERATING HUMIDITY RANGE	20% to 85% RH

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

