



TAK-TY® CABLE TIE MOUNT

ABMT-S6-C69

The screw applied mount for Tak-Ty hook and loop cable ties in natural uses #6 (M3) screw. It is 1.12" long x 1.12" wide (28.5 x 28.5 mm) and made of flame-retardant nylon 6.6, which increases mechanical strength, heat and wear resistance, and stiffness. It is used with HLT/HLS Tak-Ty hook and loop cable ties, is designed for indoor environments, and comes in packages of 100.

Specifications

Application	Use With Hook and Loop Cable Ties
Product Type	Cable Tie Mount
Color	Natural
Flammability Rating	UL94V-0
Environment	Indoor
Material	Nylon 6.6
Maximum Compatible Panel Thickness (In.)	0.04
Maximum Compatible Panel Thickness (mm)	1
Maximum Operating Temperature (°C)	110
Maximum Operating Temperature (°F)	230
Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Mount Method	Screw-On
Mounting Hole Thread Size	#6
Overall Height (In.)	0.34
Overall Height (mm)	8.6
Overall Length (In.)	1.12
Overall Length (mm)	28.4
Overall Width (In.)	1.12
Overall Width (mm)	28.4
Resistance Properties	Heat-Resistant
Standards Met	RoHS Compliant
Static Load Capacity (kg)	0.2
Static Load Capacity (lb)	0.38
Sub Brand	Tak-Ty®

Packaging Detail

UPC	07498385992
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0705
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.7051