

CUSA442TC38, 2-Hole Copper Stacking Adapter, 3/8" Stud, 1" Spacing

By Burndy

Catalog # [CUSA442TC38](#)



Copper, tin plated, 2 hole (3/8" stud - 1" hole spacing), up to 35kV, used to elevate terminals for vertical parallel conductor accommodates. Adapter length 1.75", width 1.12", height 1.50

Features

- For use on terminals made from copper
- Designed specifically for stacking standard terminals, uses include placing the stacking adapter on the mounting plate and a terminal on top of the stack adapter and bolt down, or placing a stacking adapter on a terminal pad that will be mounted to a bus bar or mounting plate and a terminal on top of the stacking adapter, and bolt down
- May be used with standard NEMA two and four hole terminals, to stack four hole NEMA terminations requires use of two stacking adapters assembled side-by-side
- Stacking adapters are clearly marked

Application

Stacking Adapter

General

Catalog Number	CUSA442TC38
Connector Type	STACKING ADAPTER
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYSTACK™
Type	Standard Barrel, Tin Plated
UPC	781810249246
UPC 12 Digit	7818102492466

Dimensions

Dimension - Bolt Size fraction	3/8
Dimension - Height inch	1.50 in
Dimension - Height mm	38.1 mm
Dimension - Hole Size fraction	3/8
Dimension - L Length Overall mm	44 mm
Dimension - Length Overall inch	1.75 in

Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - Width inch	1.12 in
Dimension - Width mm	28 mm
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Voltage - Maximum	35000
-------------------	-------

Conductor Related

Conductor - AL Str Size	1000 KCMIL
Conductor - Copper Str Compact Size	1000 KCMIL
Conductor - Copper Str Size	1000 KCMIL
Conductor - Copper Str Size Range	10 AWG - 750 kcmil
Conductor - Material	COPPER
Conductor Type	CODE/FLEX
Wire Size	1000 KCMIL

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	1
Minimum Pack Quantity	1

Product Assets

[3D Models - CUSA442TC38_MODEL-PDF](#)
[3D Models - CUSA442TC38_MODEL-STEP](#)
[3D Models - CUSA442TC38_MODEL-IGES](#)

Catalogs - BURNDY Master Catalog - Section C - Compression
Connections
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - SC212660-01
Specifications - CUSA442TC38



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
BRDY-CUSA442TC38-SPEC-EN | REV 10/2024