



Panduct® F2X2LG6 Base Wiring Duct

F2X2LG6

The F2X2LG6 Panduct Lead-Free PVC Narrow Slot Wiring Duct features a narrow slot/finger design that closely matches the spacing of high-density components. Upper and lower scorelines allow for easy finger/sidewall section removal. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). Mounting holes provided. Lead-free PVC. 2" x 2" (50.8 mm x 50.8 mm) and 6' (1.83 m) long. Cover sold separately. Color Light Gray.

Specifications

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
Product Type	Base Wiring Duct
Color	Light Gray
Cover Part Number	C2LG6
Flammability Rating	UL94V-0
Includes	Base Only
Standards Met	RoHS Compliant, UL Recognized, CE Compliant; CSA Approved
Material	PVC
Material Properties	Lead-Free
Mount Method	Mounting Holes
Measurement System	Imperial
Wiring Duct Style	Narrow Slot Wiring Duct
Wiring Duct Type	F
Overall Height (In.)	2.12
Overall Height (mm)	53.8
Overall Length (ft.)	6
Overall Length (m)	1.8
Overall Width (In.)	2.25
Overall Width (mm)	57.2
Slot Width (In.)	0.2
Slot Width (mm)	5
Sub Brand	Panduct®
Part Features	Narrow finger and slot design closely matches the spacing of high-density components. Upper and lower scorelines allows easy finger and sidewall section removals. Double restricted slot design for retaining wires, eliminating hassle and saving time

Packaging Detail

UPC	07498337553
Std. Pkg. Qty.	6
Std. Pkg. Volume (cf)	0.1319
Std. Ctn. Qty.	120
Std. Ctn. Volume (cf)	2.6371