



FIBER-DUCT™ UNDERFLOOR PEDESTAL

FUSB

Used to support the 2x2 and 4x4 Fiber-Duct™ Systems by attaching to underfloor pedestal (not included). Use on pedestals up to 1" in diameter. Bracket contains hardware to attach to pedestal and hardware for mounting channel to bracket.

Specifications

Application	(1) The Fiber-Duct 2X2 and 4X4 Routing Systems are Comprised of Channel, Fittings, and Brackets Designed to Segregate, Route, and Protect Fiber Optic Cable and Copper Cabling. (2) it is Suited for Data Center Applications.
Product Type	Underfloor Pedestal
Sub Brand	Fiber-Duct™
Color	Silver
For Use With	2x2 and 4x4 Fiber-Duct Systems
Includes	(1) Bracket, (2) 1/4-20x2x1 1/8x1 Round Bend U-Bolts, (2) 1/4 - 20 Hex Nuts, (2) 1/4 Helical Spring Lockwashers, (2) #10-32x1/2 Pan Head Slotted Machine Screws, (2) #10 Helical Spring Lockwashers, (2) #10-32 Hex Machine Screw Nuts
Material	Steel
Number of Pieces	15
Overall Height (In.)	4.49
Overall Height (mm)	114
Overall Length (In.)	6.74
Overall Length (mm)	171.2
Overall Width (In.)	2
Overall Width (mm)	50.8
Standards Met	UL Listed To 2024 Optical Fiber Cable Routing Assemblies, UL Recognized (File No. E147128) Slotted Wall, CSA Certified (File No. 016446 0 000) Slotted Wall, LP-CSISPEC-FD-1
System Dimensions	2x2, 4x4
Angle	90°
Series Type	2 x 2 and 4 x 4 Fiber-Duct Brackets
Part Features	Fastest installations, easy to maintain, system strength, versatility, Cable protection.

Packaging Detail

UPC	07498362539
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0456
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.4563