



Dome-Top® BT3S-C0 Barb Tie, Black, UV PA6.6, 12"L, 50lb, PK100

BT3S-C0

The BT3S-C0 Dome-Top® barb tie, features a unique patented design with its round smooth edges. Paired with the stainless steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Standard cross section, 12.0" (305mm) length. Appropriate for Indoor/Outdoor use, made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 100.

Specifications

Product Type	Cable Tie
Sub Brand	Dome-Top®
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	12
Overall Length (mm)	305
Body Width (In.)	0.185
Body Width (mm)	4.7
Body Thickness (In.)	0.052
Body Thickness (mm)	1.2
Maximum Bundle Diameter (In.)	3
Maximum Bundle Diameter (mm)	76
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL 62275 (File E56854), CSA-C22.2 No. 62275, 11130200, NRC 10CFR50, QPL-AS23190, CSA Certified, RoHS Compliant

Specifications (continued)

For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
--------------	--

Packaging Detail

UPC	07498341207
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0534
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.5339