FDT-AJ012NXT1000



iFDT Indoor Fiber Distribution Terminal, 12-fiber, SC/APC, loose tube OSP cable, 1000 feet

- Compact and secure family of enclosures by connecting fiber cables at MDUs
- Integrated splice trays offer flexible splice management for individual or mass splicing
- Dual-hinged design ensures separation of owner/client network segments
- Robust steel construction protects fibers against damage and ensures network reliability
- Slotted cable entrance ports allow for rapid cable installation and pass-through capability

Product Classification

Regional Availability	North America
Product Type	Fiber distribution terminal
Product Series	IFDT

General Specifications

Functionality	Patching | Splicing
Adapters, quantity	12
Cable Entry Location	Bottom right | Top right
Cable Type	OSP - Loose Tube
Color	Putty white
Front Door Type	Double hinged
Growth Configuration	Fully loaded
Interface	SC/APC
Interface, stub	No connector
Lock Type	Padlock ready
Mounting	Wall

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: July 17, 2026

FDT-AJ012NXT1000

Port, quantity	12

Dimensions

Height	184.15 mm | 7.25 in
Width	299.72 mm | 11.8 in
Depth	82.55 mm | 3.25 in
Cable Length	304.8 m | 1,000 ft

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: July 17, 2026

FDT-AJ012NXT1000

Ordering Tree

FDT- __ __ __ __ __ NX __ __ __ __ 0

Enclosure Type/Capacity

A	iFDT-12	12 Fiber
B	iFDT-24	24 Fiber
C	iFDT-48	48 Fiber
D	iFDT-72	72 Fiber
E	iFDT-96	96 Fiber

Connector/Adapter Style

Singlemode	
J	SC/APC
N	SC/UPC
K	LC/UPC
Multimode	
9	MMSC
6	MMLC

Splice Tray

0	No Tray
2	Heat Shrink Fusion
3	Mechanical/Ribbon

Fiber Count

06	6 Fiber
12	12 Fiber
24	24 Fiber
48	48 Fiber
72	72 Fiber
96	96 Fiber

Stub Length

000	0 Feet
025	25 Feet
100	100 Feet
200	200 Feet
300	300 Feet
500	500 Feet

Cable Type

Pigtails	
A	Bare ribbon pigtail assy
B	12 Fiber Soft-Walled Bundle*
Stubs	
S	Ribbon OSP w/Conn
R	Ribbon IFC w/Conn
T	Loose Tube OSP w/Conn
V	Loose Tube IFC w/Conn

* 900 micron fiber bundled in a soft jacket.

Material Specifications

Finish	Powder coated
Material Type	Steel

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: July 17, 2026

COMMSCOPE® an Amphenol company

FDT-AJ012NXT1000

Optical Specifications

Fiber Mode	Singlemode

Environmental Specifications

Environmental Space	Indoor
Qualification Standards	NEMA, Type 12 | Telcordia GR-2898-CORE

Packaging and Weights

Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: July 17, 2026

COMMSCOPE® an Amphenol company